



Ph: 888-738-9761

Seal Tight Solutions, Inc.

www.sealtightsolutions.com

**THE PERFECT COMBO FOR A
CLEAN, DRY, BRIGHT
CRAWLSPACE FLOOR**

- Prevents liner from "sticking" to soil
- Enhances water drainage beneath liner
- 100% polypropylene fibers - won't rot or decay
- Cushions floor - protects liner, hands and knees

STST Drain Fabric

- 100% pure virgin resins.
- Seals out moisture and soil gases.
- Antimicrobial - Won't support mold growth.
- Class A / Class1 fire rated.
- Nylon reinforced - Won't rip, rot or decay.
- 25 yr. manufacturer warranty.

STST 20-22mil Floor Liner

STS 20-22mil Floor Liner

PROPERTY	TEST METHOD	SPECS
Appearance	Visual	White / white
Thickness	ASTM D-2103	20-22 mil
Weight per 1000'	ASTM D-751	92 lbs
Construction	Reinforced Laminate Virgin Grade Resins	
3" Load @ Break	ASTM D-882	120 lbs/2100 psi
3" Elongation @ Break	ASTM D-882	380%
Mold / Fungus Growth	STD-810 D	
Water Vapor Transmission	ASTM E-96	0.019 usp

STS Drain Fabric

PROPERTY	TEST METHOD	SPECS
Weight	Scale	8 oz/yd ²
Tensile Strength	ASTM D-4632	205 lbs
Elongation @ Break	ASTM D-4632	50%
Mullen Strength	ATSM D-3786	400 psi
Puncture Strength	ASTM D-4833	130 lbs
Trapezoidal Tear	ASTM D-4533	85 lbs
Apparent Opening Size	ASTM O-4751	80 US Sieve
Permittivity	ASTM D-4491	1.40 sec
UV Resistance, % Retained	ASTM D-4355	70%
Flow Rate	ASTM D-9941	90 gal/min/sf